911		
PORSCHE  2020 Porsche Models  Technical Data	2020 911 Carrera S Cabriolet	2020 911 Carrera 4S Cabriolet
Engine		
Engine layout Engine type Cylinders Valves per cylinder Construction Fuel injection Fuel Displacement (Liters) Bore/Stroke (mm/mm) Maximum power output @ engine speed Maximum torque @ engine speed	Rear Engine Boxer, twin-turbo 6 4 Aluminum crankcase and heads Direct Fuel Injection (DFI) Premium 3.0 I 91.0 mm / 76.4 mm 443 hp @ 6500 390 lbft. @ 2300-5000	Rear Engine Boxer, twin-turbo 6 4 Aluminum crankcase and heads Direct Fuel Injection (DFI) Premium 3.0 I 91.0 mm / 76.4 mm 443 hp @ 6500 390 lbft. @ 2300-5000
Maximum engine speed	7500	7500
Compression ratio (tolerance +/- 0.3) Output per liter Lubrication Power to weight ratio (lb/hp) Drivetrain Chassis & Suspension	10.2 : 1 148 hp Integrated dry-sump 8.0 Rear-wheel drive	10.2 : 1 148 hp Integrated dry-sump 8.2 Active all-wheel drive
Body	Monocoque lightweight body in a combination of steel,	Monocoque lightweight body in a combination of
	aluminum, and magnesium	steel, aluminum, and magnesium
Front Axle Rear Axle Steering System Steering Ratio Steering Ratio with rear-axle steering Turning Circle	MacPherson strut with anti-roll bar Aluminum multi-link with anti-roll bar Variable ratio electromec. power steering 15.0:1 (on-center) to TBD 14.1:1 (on-center) to TBD 36.8 ft / 35.8 ft. (with rear axle steering)	MacPherson strut with anti-roll bar Aluminum multi-link with anti-roll bar Variable ratio electromec. power steering 15.0:1 (on-center) to TBD 14.1:1 (on-center) to TBD 36.8 ft / 35.8 ft. (with rear axle steering)
Brakes & Wheels	30.0117 33.011. (With real date steering)	50.0 H. / 50.0 H. (Withheat date steering)
Caliper type	Aluminum monobloc fixed-caliper brake	Aluminum monobloc fixed-caliper brake
Rotor material Caliper color Number of pistons (front/rear) Rotor diameter (front/rear) mm Rotor thickness (front/rear) mm Caliper type (optional PCCB system) Rotor material (optional PCCB system) Caliper color (optional PCCB system) Number of pistons (front/rear - optional PCCB system) Rotor diameter (front/rear - optional PCCB system)	Steel Red 6 / 4 350 mm / 350 mm 34 mm / 28 mm Aluminum monobloc fixed-caliper brake Carbon-ceramic composite Yellow 6 / 4 410 mm / 390 mm	Steel Red 6 / 4 350 mm / 350 mm 34 mm / 28 mm Aluminum monobloc fixed-caliper brake Carbon-ceramic composite Yellow 6 / 4 410 mm / 390 mm
Rotor thickness (front/rear - optional PCCB system) mm	36 mm / 32 mm	36 mm / 32 mm
Standard wheels Wheels (front/rear) Tires (front/rear)	20" / 21" Carrera S 8.5J x 20" / 11.5J x 21" 245/35 ZR 20 / 305/30 ZR 21	20" / 21" Carrera S 8.5J x 20" / 11.5J x 21" 245/35 ZR 20 / 305/30 ZR 21
Transmission		
Number of gears Transmission type Ratios	8 8-speed dual-clutch PDK	8 8-speed dual-clutch PDK
1st 2nd 3rd 4th 5th 6th 7th Reverse Final drive ratio front axle	4.89 3.17 2.15 1.56 1.18 0.94 0.76 3.96 0	4.89 3.17 2.15 1.56 1.18 0.94 0.76 3.96 3.33
Rear Axle Ratio / rear constant transaxle ratio Clutch 1/Clutch 2 diameter (inches)	3.39 / 0.92 8.7 / 6.6 inches (PDK)	3.39 / 0.92 8.7 / 6.6 inches (PDK)
Dimensions, Aerodynamics, & Weight	0.7 / 0.0 IIICHES (FDK)	0.7 / 0.0 IIIGIES (FDK)

Length with standard PASM Sport Suspension (inches/mm)	177.9 in. / 4519 mm	177.9 in. / 4519 mm
Length with optional PASM Sport Suspension (inches/mm)	178.4 in. / 4530 mm	178.4 in / 4530 mm
Wheelbase (inches/mm)	96.5 in. / 2450 mm	96.5 in. / 2450 mm
Width w/ mirrors (inches/mm)	79.7 in. / 2024 mm	79.7 in. / 2024 mm
Width w/o mirrors (inches/mm)	72.9 in. / 1852 mm	72.9 in. / 1852 mm
Height with standard PASM suspension (inches/mm)	51.2 in. / 1299 mm	51.2 in. / 1299 mm
Track width front (inches/mm)	62.5 in. / 1589 mm	62.5 in. / 1589 mm
Track width rear (inches/mm)	61.2 in. / 1557 mm	61.2 in. / 1557 mm
Legroom (inches)	TBD	TBD
Headroom (inches)	TBD	TBD
Cargo area volume (cuft.) front trunk	132 I / 4.66 cuft.	132 I / 4.66 cuft.
Cargo area volume (cuft.) rear seats	163 I / 5.75 cuft.	163 I / 5.75 cuft.
Fuel tank capacity - refill volume (gal)	16.9 gal.	17.6 gal.
Curb weight (lbs)	3537 lbs.	3641 lbs.
Gross Vehicle Weight (lbs)	4497 lbs.	4553 lbs.
Payload range (lbs)	960 lbs.	912 lbs.
Performance		
Top track speed PDK (mph)	190 mph	188 mph
Acceleration 0-60 PDK (sec)	3.7 sec.	3.6 sec.
Acceleration 0-60 PDK with Launch Control (sec)	3.5 sec.	3.4 sec.
Quarter mile time PDK (sec)	12.1 sec.	12.0 sec.
Quarter mile time PDK with Launch Control (sec)	11.9 sec.	11.8 sec.
Fuel Economy/Rating		
Rating	-	-
City	available closer to U.S. market launch	available closer to U.S. market launch
Highway	available closer to U.S. market launch	available closer to U.S. market launch
Combined	available closer to U.S. market launch	available closer to U.S. market launch