	718 Cayman	718 Cayman S	
ngine			
Туре	Turbocharged flat four-cy	linder engine	
No. of cylinders		4	
Valves/cylinder		4	
Displacement	1988 cm ³	2497 cm ³	
Bore	91.0 mm	102.0 mm	
Stroke	76.4	mm	
Max. power output	300 hp	350 hp	
at engine speed	6,500) rpm	
Max. torque	280 lbft.	309 lbft.	
at engine speed	1,950 – 4,500 rpm	1,900 – 4,500 rpm	
Max. output per liter	151 hp/l	140 hp/l	
Compression ratio	9.	9.5:1	
Maximum engine speed	7,500 rpm		
Cooling system	Water cooling with thermal mana	agement and water pump that operates o	
Valve control	Camshaft adjustment and adjustment for intake and exhaus	VarioCam Plus valve stroke st	
Oil supply	Integrated dry sump lubrication a	Integrated dry sump lubrication and demand-controlled oil pump	
Engine charging	Single turbocharger, 19 psi (1.3 bar) max. boost	Single turbocharger with VTG, 16.7 psi (1.15 bar) max. boost	
Intercooling	Water-to-ai	r intercooling radiators and a water intercooler)	
Exhaust system	Dual-branch exhaust system with central stainless steel tailpipe	Dual-branch exhaust system with central stainless steel dual tailpipes	
Emission control system	Two three-way catalytic converters and on- board diagnostics for monitoring the emission control system		
Fuel management	Gasoline Direct Fuel Injection (DFI)		
Drive system	Mid-engine, rea	r-wheel drive	

	718 Cayman	718 Cayman S
ower transmission		
Transmission	Six-speed manual transmission wit flywheel; optional seven-speed D	
Clutch diameter	Manual 9.4 in. (240 m	nm); PDK 202/153 mm
Gear ratios	Manua	ıl / PDK
1st gear	3.31	/3.91
2nd gear	1.95	/2.29
3rd gear	1.41	/1.65
4th gear	1.13	/1.30
5th gear	0.95	/1.08
6th gear	0.81	/0.88
7th gear	-/C	0.62
Reverse gear	3.00	/3.55
Rear axle	3.89	/3.62
 Chassis		
Front axle	Lightweight spring-strut suspen	sion (MacPherson type)
Rear axle	Lightweight Ma	acPherson suspension
Steering	Electromechanical power steel and steering	S S
Steering ratio	15.0:1 (on-cer	nter) to 12.5:1
Steering wheel diameter	14.8 inches (375 mm)) / opt. 14.1 inches (360 mm)
Turning radius	36 ft. (10.98 m)
Driving stability system		t (PSM) incl. ABS with extended functions

	718 Cayman	718 Cayman S
Brakes		
Brake system	Four-piston aluminium monoblock fixed caliper brakes, front and rear	Four-piston aluminium monoblock fixed caliper brakes, front and rear
Brake discs, front axle	Grey cast iron; vented a	and perforated
Diameter	13.0 inche	s (330 mm)
Thickness	1.1 inches (28 mm)	1.3 inches (34 mm)
Brake discs, rear axle	Grey cast iron; vented a	and perforated
Diameter	11.8 inche	s (299 mm)
Thickness	0.8 inche	s (20 mm)
Wheels and tires		
Wheels with tires, front	8 J x 18 ET 57 with 235/35 ZR 18 tires	8 J x 19 ET 57 with 235/40 ZR 19 tires
Wheels with tires, rear	9.5 J x 18 ET 49 with 265/45 ZR 18 tires	10 J x 19 ET 45 with 265/40 ZR 19 tires
Dimensions		
Length	172.4 inches (43	79 mm)
Width (with door mirrors)	70.9 inches (1801 mm)	/ 78.5 inches (1994 mm)
Height	51.0 inches (1295 mm)	51.0 inches (1295 mm)
Wheelbase	97.4 inches (24	75 mm)
Track width, front (for wheel size)	59.6 inches (1515 mm) (18")	59.6 inches (1515 mm) (19")
Track width, rear (for wheel size)	60.3 inches (1532 mm) (18")	60.6 inches (1540 mm) (19")
Luggage capacity and we	eights Manual/	/PDK
Luggage capacity	5.3 cuft. (150 I) front, 9.	7 cuft. (275 I) rear
Unladen weight	2944 / 3010 lbs.	2988 / 3054 lbs.
Gross vehicle weight rating	3649 / 3715 lbs.	3671 / 3737 lbs.
Power-to-weight ratio	9.8 / 10.0 lb./hp	8.5 / 8.7 lb./hp

	718 Cayman	718 Cayman S
Performance	Manual/PDK	
Top track speed	170/170 mph	177/177 mph
Acceleration		
0-60 mph	4.9/4.7 s	4.4/4.2 s
0 – 60 mph with Sport+	-/4.5 s	-/4.0 s
0 – 100 mph	11.3/11.1 s	9.7/9.5 s
0 – 100 mph with Sport+	-/10.8 s	-/9.2 s
Quarter mile	13.4/13.2 s	12.8/12.6 s
Quarter mile with	-/13.0 s	-/12.4 s
Fuel tank capacity (refuelling	14.3 gallons (54 l) / 16.9	10.0 gallone (C4.1)
volume)	gallons (64 I) optional	16.9 gallons (64 l)
		16.9 gallons (64 I)
volume)		16.9 gallons (64 I)
volume)		0.31
volume) Aerodynamics	gallons (64 I) optional 0.30	
volume) Aerodynamics Drag coefficient cd	gallons (64 I) optional 0.30	0.31
Aerodynamics Drag coefficient c _d Frontal area A	gallons (64 I) optional 0.30 2.0	0.31 01 m ²
Aerodynamics Drag coefficient c _d Frontal area A c _d x A:	gallons (64 I) optional 0.30 2.0	0.31 01 m ² 0.62
Aerodynamics Drag coefficient cd Frontal area A cd x A: EPA-rated fuel economy	gallons (64 I) optional 0.30 2.0 0.60 Manua	0.31 01 m ² 0.62