## 2010 Models

## **Specifications**

	Cayman Cayman S			
Engine Concept	Horizontally opposed, mid-mounted six-cylinder			
Construction	Aluminium engine block and cylinder head			
Valvetrain	Four overhead camshafts, four valves per cylinder, variable intake valve timing and lift control (VarioCam Plus), hydraulic valve play compensation			
Intake System	Sequential Multipoint Fuel Injection	Direct Fuel Injection (DFI)		
Lubrication	Integrated dry-sump			
Management	Motronic® with six coils, sequential multipoint fuel injection			
Electrical System	12-volt, 2100-watt alternator, 60Ah battery	12-volt, 2100-watt alternator, 70Ah battery		
Fuel	Premium Unleaded			
Bore	3.5 in. (88 mm)	3.8 in. (97 mm)		
Stroke	3.1 in. (77.5 mm)			
Displacement	2893 (2.91)	3436 (3.41)		
Max. Horsepower	265 @ 7200	320 @ 7200		
Max. torque (lb.ft.)	221 @ 4400-6000	273 @ 4750		
Engine redline	7500			
Compression ratio	11.5:1	12.5:1		
Output per liter	91.6 hp/l	93.1 hp/l		
Drivetrain	rear-wheel drive			
Power unit	Engine and transmission bolted together to form common drive unit, engine power transmitted via driveshafts			

Occarloss		DD1/		5514	
Gearbox	Manual	PDK	Manual	PDK	
Gear Ratios			•		
1	3.667	3.909	3.308	3.909	
2	2.050	2.292	1.950	2.292	
3	1.407	1.654	1.407	1.654	
4	1.133	1.303	1.133	1.303	
5	0.972	1.081	0.950	1.081	
6	0.841	0.881	0.081	0.881	
7	-	0.617	-	0.617	
R	3.333	3.545	3.000	3.545	
Final Drive	3.875	3.250	3.889	3.250	
Body	Two-seat coupe, monocoque structure, lightweight, hot-galvanized all-steel body shell				
Drag Coefficient	0.29	0.29	0.29	0.30	
Front Suspension	Independent MacPherson struts with alumium control arms, coil springs, stabilizer bar and negative steering-roll radius				
Rear Suspension	Independent MacPherson struts with aluminum control arms and stabilizer bar; toe-angle control				
Brakes	Four-piston monobloc, aluminum fixed calipers front and rear, discs internally vented and cross-drilled				
Front Brake Discs	12.52 (318 mm)				
Rear Brake Discs	11.77 in (299 mm)				
Wheels and Tires					
Front	7.0 J x 17" / 205/55		8J x 18" / 235/40		
Rear	8.5J x 17" / 235/50		9J x 18" / 265/40		
Exterior Dimensions					
Front Track	58.7 in.		58.5 in.		
Rear Track	60.4	60.4 in.		60.2 in.	
Wheelbase	95.1 in. (2415 mm)				
Length	172.3 in.				
Width	70.9 in.				

Height	51.3 in.		51.4 in.		
Turning Circle	36.4 ft (11.1 m)				
Ground Clearance	5.1 in., 130 mm		5.0 in., 126 mm		
(with PASM)	(4.7 in., 120 mm)		(4.6 in., 116 mm)		
Interior Dimensions					
Headroom	37.8 in. (959 mm)				
Legroom	33.5 in. (850 mm)				
Shoulder Room	51.5 in. (1308 mm)				
Elbow Room	53.4 in (1355 mm)				
Luggage Capacity	9.9 cu.ft. (280 liters)				
Front Trunk	5.3 cu.ft.(150 liters)				
Rear Trunk	9.2 cu.ft. (260 liters)				
Fuel Tank Capacity	16.9 gal (64 liters)				
Curb Weight	Manual	PDK	Manual	PDK	
[ lbs.]	2932	2998	2976	3031	
Fuel economy city/hwy [mpg]	19/27	20/29	19/26	20/29	
Top Track Speed	165 mph	163 mph	172 mph	171 mph	
Acceleration					
0-60 mph	5.5 sec.	5.4 sec.	4.9 sec.	4.8 sec.	
0-60 mph PDK w/Sport					
Chrono Package Plus	5.2 sec.		4.6 sec.		