2010 Models

Specifications

-	Cayenne	Cayenne S	
Engine Concept	Water-cooled, front-mounted V6	Water-cooled, front-mounted V8	
Construction	Cast iron engine block and aluminum alloy cylinder heads	Aluminum alloy engine block and cylinder heads	
Valvetrain	Dual overhead camshafts, 4 valves per cylinder, infinite variable valve timing on intake and outlet side	Dual overhead camshafts, 4 valves per cylinder, VarioCam Plus valve timing	
Intake System	Direct Fuel Injection (DFI)		
Lubrication	Forced-feed lubrication with wet sump		
Management	MED 9.1	EMS SDI 4.1	
Electrical System	2,520 watt alternator, 70 Ah battery	2,660 watt alternator, 95 Ah battery	
Fuel	premium unleaded		
Bore	3.50 in. (89 mm)	3.78 in. (96 mm)	
Stroke	3.80 in. (96.4 mm)	3.27 in. (83 mm)	
Displacement	3,598 cc (3.6l)	4,806 cc (4.8l)	
Max. Horsepower	290 hp @ 6200 rpm	385 hp @ 6200 rpm	
Max. torque (lb.ft.)	273 lb.ft. @ 3000 rpm	369 lb.ft. @ 3500 rpm	
Engine redline	6700 rpm		
Compression ratio	12.3:1	12.5:1	
Output per liter	59.2	58.9	

Drivetrain	6-speed manual/ 6-speed Tiptronic S with all-wheel drive		6-speed Tiptronic S with all-wheel drive	
Gear Ratios	Manual	Tiptronic S	Tiptronic S	
1	4.68	4.15	4.15	
2	2.53	2.37	2.37	
3	1.69	1.56	1.56	
4	1.22	1.16	1.16	
5	1.00	0.86	0.86	
6	0.84	0.69	0.69	
R	4.27	3.39	3.39	
Final Drive	3.70	4.30	3.55	
Reduction Gear	2.7:1			
Clutch Diameter	0.24 in. (260 mm10.24 in. (260 mm		10.24 in. (260 mm)	
Body	Monocoque with all-steel lightweight body shell, hot-galvanized on both sides			
Drag Coefficient	0.35		0.35	
Turning Circle	38.39 ft.			
Front Suspension	Fully independent double wishbone with rack and pinion steering (power-assist)			
Rear Suspension	Fully independent multi-link with rack and pinion steering (power-assist)			
Brakes	Ventilated discs front and rear			
Front	Six-pistion aluminum monobloc fixed calipers			
Rear	Four-piston aluminum monobloc fixed calipers			
Front Brake Discs Rear Brake Discs	2.99 in. x 1.10 in. (330 mm x 32 mm		· · · · · · · · · · · · · · · · · · ·	
Wheels and Tires	2.99 in. x 1.10 in. (330 mm x 28 mm 12.99 in. x 1.10 in. (330 mm x 28 mm)			
Front	75.1x17.with	1 235/65 R 17	8 J x 18 with 255/55 R 18	
Rear	7.5 J x 17 with 235/65 R 17		8 J x 18 with 255/55 R 18	
Exterior Dimensions				
Front Track	65.16 in. (1655 mm)		64.84 in. (1647 mm)	
Rear Track	65.75 in. (/	65.43 in. (1662 mm)	
Wheelbase	112.40 in. (2855 mm)			

Length	188.90 in. (4798 mm)		
Width	75.91 in. (1928 mm)		
Height	66.89 in. (1699 mm)		
Ground Clearance, steel			
suspension	8.6 in.		
Ground Clearance, air			
suspension, range vs.	6.34 - 10.67 in. vs 8.46 in.		
normal ride height			
Interior Dimensions			
Headroom, F/R	38.7 in. (983 mm)/38.66 in. (982 mm)		
Legroom, F/R	40.6 in. (1032 mm)/36 in. (914 mm)		
Shoulder Room, F/R	58.5 in. (1485 mm)/56.7 in. (1441 mm)		
Elbow Rom F/R	60.4 in (1534 mm)/58.5 in. (1487 mm)		
Luggage Capacity			
Rear Seat Up	19.1 cu.ft.		
Rear Seat Down	62.5 cu.ft		
Fuel Tank Capacity	26.4 gal.		
	Manual	Tiptronic S	Tiptronic S
Curb Weight	4762 lbs.	4784 lbs.	4949 lbs.
GVWR	6493 lbs.	6493 lbs.	6790 lbs.
Maximum Load	1731 lbs.	1709 lbs.	1841 lbs.
Towing Capacity	7716 lbs.		
Fuel economy city/hwy	14/20	14/20	13/19
[mpg]			
Top Track Speed	41 mph (227 km/ł	41 mph (227 km/ł	155 mph (250 km/h)
Acceleration			
0-60 mph (0-96 km/h)	7.5 sec.	7.9 sec.	6.4 sec.