


	Panamera	Panamera 4	Panamera 4 Sport Turismo	Panamera 4 Executive	Panamera 4 E-Hybrid	Panamera 4 E-Hybrid Sport Turismo	Panamera 4 E-Hybrid Executive	Panamera 4S	Panamera 4S Sport Turismo	Panamera 4S Executive	Panamera Turbo	Panamera Turbo Sport Turismo
MY18 MSRP	\$85,000	\$89,600	\$96,200	\$96,300	\$99,600	\$104,000	\$104,100	\$103,000	\$109,200	\$113,900	\$150,000	\$154,000
<b>Engine</b>												
Engine layout	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine
Engine type	Mono-turbo V6	Mono-turbo V6	Mono-turbo V6	Mono-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V6	Twin-turbo V8
Cylinders	6	6	6	6	6	6	6	6	6	6	6	8
Valves per cylinder	4	4	4	4	4	4	4	4	4	4	4	4
Construction												
Fuel injection	DFI	DFI	DFI	DFI	DFI	DFI	DFI	DFI	DFI	DFI	DFI	DFI
Fuel	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium	Premium
Displacement (liters)	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	2.9	4.0
Bore/Stroke (mm)	84.5 x 89.0	84.5 x 89.0	84.5 x 89.0	84.5 x 89.0	84.5 x 86.0	84.5 x 86.0	84.5 x 86.0	84.5 x 86.0	84.5 x 86.0	84.5 x 86.0	84.5 x 86.0	86.0 x 86.0
Maximum power (hp) @ engine speed (1/min)	330 @ 5,400 - 6,400	330 @ 5,400 - 6,400	330 @ 5,400 - 6,400	330 @ 5,400 - 6,400	330 @ 5,250 - 6,500	330 @ 5,250 - 6,500	330 @ 5,250 - 6,500	440 @ 5,650-6,600	440 @ 5,650-6,600	440 @ 5,650-6,600	550 @ 5,750-6,000	550 @ 5,750-6,000
Maximum torque (lb.-ft.) @ engine speed (1/min)	331 @ 1,340 - 4,900	331 @ 1,340 - 4,900	331 @ 1,340 - 4,900	331 @ 1,340 - 4,900	331 @ 1,750 - 5,000	331 @ 1,750 - 5,000	331 @ 1,750 - 5,000	405 @ 1,750-5,500	405 @ 1,750-5,500	405 @ 1,750-5,500	567 @ 1,960-4,500	567 @ 1,960-4,500
Maximum engine speed (1/min)	6,500	6,500	6,500	6,500	6,800	6,800	6,800	6,800	6,800	6,800	6,800	6,800
Compression ratio	11.2 : 1	11.2 : 1	11.2 : 1	11.2 : 1	10.5 : 1	10.5 : 1	10.5 : 1	10.5 : 1	10.5 : 1	10.5 : 1	10.1 : 1	10.1 : 1
Electric Motor: Maximum power (hp)					136 @ 2,800	136 @ 2,800	136 @ 2,800					
Electric Motor: Maximum torque (lb.-ft.)					295 @ 100 - 2,300	295 @ 100 - 2,300	295 @ 100 - 2,300					
Total Output: ICE + Electric Motor (hp)					462 @ 6,000	462 @ 6,000	462 @ 6,000					
Total Output: ICE + Electric Motor (lb.-ft.)					516 @ 1,100 - 4,500	516 @ 1,100 - 4,500	516 @ 1,100 - 4,500					
Power to weight ratio (lb/hp)	12.1	12.4	12.6	12.9	10.4	10.5	10.7	9.4	9.6	9.9	8.0	8.2
hp/liter	110.0	110.0	110.0	110.0	159.3	159.3	159.3	151.7	151.7	151.7	137.5	137.5
<b>Chassis &amp; Suspension</b>												
Drivetrain	Rear-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive
Front Axle	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension
Rear Axle	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension
Steering System	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical, Power Steering Plus	Electromechanical	Electromechanical
Steering Ratio	variable	variable	variable	variable	variable	variable	variable	variable	variable	variable	variable	variable
Turning Circle (ft)	39.0 (37.4 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	40.7 (38.7 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	40.7 (38.7 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)	38.7 w/ Rear Axle Steering std.	39.0 (37.4 w/ Rear Axle Steering)	39.0 (37.4 w/ Rear Axle Steering)
<b>Brakes &amp; Wheels</b>												
Caliper type	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear
Rotor construction	steel	steel	2-piece (front)/steel (rear)	steel	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)	2-piece (front)/steel (rear)
Caliper color	Black	Black	Black	Black	Acid Green	Acid Green	Acid Green	Titanium Grey	Titanium Grey	Titanium Grey	Titanium Grey	Red
Number of pistons (front/rear)	6/4	6/4	6/4	6/4	6/4	6/4	6/4	6/4	6/4	6/4	6/4	6/4
Rotor diameter (front/rear) mm	350/330	350/330	390/365	350/330	390/365	390/365	390/365	360/330	390/365	360/330	410/380	410/380
Rotor thickness (front/rear) mm	34/28	34/28	38/28	34/28	38/28	38/28	38/28	36/28	38/28	36/28	38/30	38/30
Wheel size and design	19" Panamera wheels	19" Panamera wheels	19" Panamera wheels	19" Panamera wheels	19" Panamera wheels	19" Panamera wheels	19" Panamera wheels	19" Panamera S wheels	19" Panamera S wheels	19" Panamera S wheels	20" Panamera Turbo wheels	20" Panamera Turbo wheels
Wheels: front/rear	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9J x 19 ET64 10.5 J x 19 ET62	9.5 J x 20 ET71 11.5 J x 20 ET68	9.5 J x 20 ET71 11.5 J x 20 ET68
Tires: front/rear	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	265/45 ZR 19 295/40 ZR 19	275/40 ZR 20 315/35 ZR 20	275/40 ZR 20 315/35 ZR 20
<b>Transmission</b>												
Number of gears	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed	8-speed
Transmission type	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II	PDK II
Gear ratios	1st	5.966	5.966	5.966	5.966	5.966	5.966	5.966	5.966	5.966	5.966	5.966
	2nd	3.235	3.235	3.235	3.235	3.235	3.235	3.235	3.235	3.235	3.235	3.235
	3rd	2.083	2.083	2.083	2.083	2.083	2.083	2.083	2.083	2.083	2.083	2.083
	4th	1.420	1.420	1.420	1.420	1.420	1.420	1.420	1.420	1.420	1.420	1.420
	5th	1.054	1.054	1.054	1.054	1.054	1.054	1.054	1.054	1.054	1.054	1.054
	6th	0.841	0.841	0.841	0.841	0.841	0.841	0.841	0.841	0.841	0.841	0.841
	7th	0.678	0.678	0.678	0.678	0.678	0.678	0.678	0.678	0.678	0.678	0.678
	8th	0.534	0.534	0.534	0.534	0.534	0.534	0.534	0.534	0.534	0.534	0.534
Reverse	5.220	5.220	5.220	5.220	5.220	5.220	5.220	5.220	5.220	5.220	5.220	5.220
<b>Dimensions, Aerodynamics, &amp; Weight</b>												
Length (inches)	198.8	198.8	198.8	204.7	198.8	198.8	204.7	198.8	198.8	204.7	198.8	198.8
Wheelbase (inches)	116.1	116.1	116.1	122	116.1	116.1	122	116.1	116.1	122	116.1	116.1
Width w/ mirrors (inches)	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
Width w/o mirrors (inches)	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3
Height (inches)	56.0	56.0	56.2	56.2	56.0	56.0	56.2	56.0	56.2	56.2	56.1	56.4
Track width front (inches)	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.2	65.8
Track width rear (inches)	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	64.5	65.0
Drag coefficient (Cd)	0.28	0.28	0.29	0.28	0.28	0.28	0.3	0.28	0.29	0.30	0.29	0.30
Cargo area volume (cu.-ft.) seats up	17.6	17.6	18.3	17.6	14.3	15	17.6	17.6	18.3	17.6	17.6	18.3
Cargo area volume (cu.-ft.) seats down	47.3	47.3	49.0	52.6	44.0	45.7	49.3	47.3	49.0	52.6	47.3	49.0
Fuel tank capacity - refill volume (gal)	23.7	23.7	23.7	23.7	21.1	21.1	21.1	23.7	23.7	23.7	23.7	23.7
Electric Battery Size (kWh)					14.1	14.1	14.1					
Curb weight (lbs)	4,001	4,079	4,144	4,266	4,784	4,828	4,960	4,123	4,221	4,365	4,398	4,486
Gross Vehicle Weight (lbs)	5,269	5,357	5,621	5,445	5,974	6,194	6,117	5,500	5,765	5,610	5,698	5,930
Payload, maximum (lbs)	1,268	1,278	1,477	1,179	1,190	1,366	1,157	1,377	1,544	1,245	1,300	1,444
<b>Performance</b>												
Top track speed (mph)	164	162	160	162	172	170	172	179	177	179	190	188
Top track speed, electric only (mph)					86	86	86					
Acceleration 0-60 mph (sec)	5.4	5.2	5.2	5.3	N/A	N/A	N/A	4.2	4.2	4.3	3.6	3.6
Acceleration 0-60 mph, w/Launch Control (sec)	5.2	5.0	5.0	5.1	4.4	4.4	4.4	4.0	4.0	4.1	3.4	3.4
Acceleration 0-60 mph, electric only					5.7	5.8	5.9					
Acceleration 1/4 mile (sec)	14.1	14.0	14.1	14.2	N/A	N/A	N/A	12.7	12.8	12.9	11.9	12.0
Acceleration 1/4 mile, w/Launch Control (sec)	13.9	13.8	13.9	14.0	12.8	12.9	13.0	12.5	12.6	12.7	11.7	11.8
<b>Fuel Economy/Rating*</b>												
City	21	21	TBD	21	TBD	TBD	TBD	21	TBD	21	18	TBD
Highway	28	27	TBD	27	TBD	TBD	TBD	28	TBD	28	25	TBD
Combined	24	23	TBD	23	TBD	TBD	TBD	23	TBD	23	21	TBD

\*US EPA estimates. Actual mileage will vary.

 <b>PORSCHE</b> Technical Data <b>MY18 MSRP</b>	<b>Panamera Turbo Executive</b>	<b>Panamera Turbo S E-Hybrid</b>	<b>Panamera Turbo S E-Hybrid Sport Turismo</b>	<b>Panamera Turbo S E-Hybrid Executive</b>
	<b>\$160,000</b>	<b>\$184,400</b>	<b>\$188,400</b>	<b>\$194,800</b>
<b>Engine</b>				
Engine layout	Front Engine	Front Engine	Front Engine	Front Engine
Engine type	Twin-turbo V8	Twin-turbo V8	Twin-turbo V8	Twin-turbo V8
Cylinders	8	8	8	8
Valves per cylinder	4	4	4	4
Construction				
Fuel injection	DFI	DFI	DFI	DFI
Fuel	Premium	Premium	Premium	Premium
Displacement (liters)	4.0	4.0	4.0	4.0
Bore/Stroke (mm)	86.0 x 86.0	86.0 x 86.0	86.0 x 86.0	86.0 x 86.0
Maximum power (hp) @ engine speed (1/min)	550 @ 5,750-6,000	550 @ 5,750-6,000	550 @ 5,750-6,000	550 @ 5,750-6,000
Maximum torque (lb.-ft.) @ engine speed (1/min)	567 @ 1,960-4,500	567 @ 1,960-4,500	567 @ 1,960-4,500	567 @ 1,960-4,500
Maximum engine speed (1/min)	6,800	6,800	6,800	6,800
Compression ratio	10.1 : 1	10.1 : 1	10.1 : 1	10.1 : 1
Electric Motor: Maximum power (hp)		136 @ 2,800	136 @ 2,800	136 @ 2,800
Electric Motor: Maximum torque (lb.-ft.)		295 @ 100 - 2,300	295 @ 100 - 2,300	295 @ 100 - 2,300
Total Output: ICE + Electric Motor (hp)		680 @ 5,750-6,000	680 @ 5,750-6,000	680 @ 5,750-6,000
Total Output: ICE + Electric Motor (lb.-ft.)		626 lb.-ft. 1,400-5,500	626 lb.-ft. 1,400-5,500	626 lb.-ft. 1,400-5,500
Power to weight ratio (lb/hp)	8.4	7.5	7.5	7.8
hp/liter	137.5	170	170	170
<b>Chassis &amp; Suspension</b>				
Drivetrain	All-wheel drive	All-wheel drive	All-wheel drive	All-wheel drive
Front Axle	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension	Aluminum double-wishbone, independent wheel suspension
Rear Axle	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension	Aluminum multi-link axle with subframe, independent wheel suspension
Steering System	Electromechanical, Power Steering Plus	Electromechanical	Electromechanical	Electromechanical, Power Steering Plus
Steering Ratio	variable	variable	variable	variable
Turning Circle (ft)	38.7 w/ Rear Axle Steering std.	39.0 (37.4 w/ Rear Axle Steering)	38.7 w/ Rear Axle Steering std.	38.7 w/ Rear Axle Steering std.
<b>Brakes &amp; Wheels</b>				
Caliper type	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear	Aluminum monobloc fixed, front and rear
Rotor construction	2-piece	Ceramic Composite	Ceramic Composite	Ceramic Composite
Caliper color	Red	Acid Green	Acid Green	Acid Green
Number of pistons (front/rear)	6/4	10/4	10/4	10/4
Rotor diameter (front/rear) mm	410/380	420/410	420/410	420/410
Rotor thickness (front/rear) mm	38/30	40/32	40/32	40/32
Wheel size and design	20" Panamera Turbo wheels	21" 911 Turbo Design	21" 911 Turbo Design	21" 911 Turbo Design
Wheels: front/rear	9.5 J x 20 ET71 11.5 J x 20 ET68	9.5 J x 21 ET71 11.5 J x 21 ET69	9.5 J x 21 ET71 11.5 J x 21 ET69	9.5 J x 21 ET71 11.5 J x 21 ET69
Tires: front/rear	275/40 ZR 20 315/35 ZR 20	275/35 ZR 21 325/30 ZR 21	275/35 ZR 21 325/30 ZR 21	275/35 ZR 21 325/30 ZR 21
<b>Transmission</b>				
Number of gears	8-speed	8-speed	8-speed	8-speed
Transmission type	PDK II	PDK II	PDK II	PDK II
Gear ratios	1st	5.966	5.966	5.966
	2nd	3.235	3.235	3.235
	3rd	2.083	2.083	2.083
	4th	1.420	1.420	1.420
	5th	1.054	1.054	1.054
	6th	0.841	0.841	0.841
	7th	0.678	0.678	0.678
	Reverse	0.534	0.534	0.534
<b>Dimensions, Aerodynamics, &amp; Weight</b>				
Length (inches)	204.7	198.8	198.8	204.7
Wheelbase (inches)	122.0	116.1	116.1	122.0
Width w/ mirrors (inches)	85.2	85.2	85.2	85.2
Width w/o mirrors (inches)	76.3	76.3	76.3	76.3
Height (inches)	56.4	56.2	56.4	56.4
Track width front (inches)	65.2	65.2	65.2	65.2
Track width rear (inches)	64.5	64.5	64.5	64.5
Drag coefficient (Cd)	0.29	0.29	0.30	0.29
Cargo area volume (cu.-ft.) seats up	17.6	14.3	15.0	14.3
Cargo area volume (cu.-ft.) seats down	52.6	44.0	45.7	49.3
Fuel tank capacity - refill volume (gal)	23.7	21.1	21.1	21.1
Electric Battery Size (kWh)		14.1	14.1	14.1
Curb weight (lbs)	4,630	5,093	5,126	5,313
Gross Vehicle Weight (lbs)	5,809	6,162	6,393	6,360
Payload, maximum (lbs)	1,179	1,069	1,267	1,047
<b>Performance</b>				
Top track speed (mph)	190	192	192	192
Top track speed, electric only (mph)		86	86	86
Acceleration 0-60 mph (sec)	3.7	N/A	N/A	N/A
Acceleration 0-60 mph, w/Launch Control (sec)	3.5	3.2	3.2	3.3
Acceleration 0-60 mph, electric only		6.0	6.1	6.3
Acceleration 1/4 mile (sec)	12.1	N/A	N/A	N/A
Acceleration 1/4 mile, w/Launch Control (sec)	11.9	11.5	11.6	11.7
<b>Fuel Economy/Rating*</b>				
City	18	TBD	TBD	TBD
Highway	25	TBD	TBD	TBD
Combined	21	TBD	TBD	TBD

\*US EPA estimates. Actual mileage will vary.