


	Macan	Macan T	Macan S	Macan GTS
 Macan Technical Data				
MY26 MSRP	\$65,400	\$71,100	\$78,900	\$94,200
Engine				
Engine layout	Front Engine	Front Engine	Front Engine	Front Engine
Engine type	turbocharged inline-4	turbocharged inline-4	twin-turbo V6, 90 degree	twin-turbo V6, 90 degree
Cylinders	4	4	6	6
Valves per cylinder	4	4	4	4
Construction	Cast Iron Crankcase and Aluminum heads	Cast Iron Crankcase and Aluminum heads	Aluminum block and heads	Aluminum block and heads
Fuel injection	DFI	DFI	DFI	DFI
Fuel	Premium	Premium	Premium	Premium
Displacement	82.5mm/92.8mm	82.5mm/92.8mm	84.5mm/86mm	84.5mm/86mm
Bore/Stroke	261 hp @ 5,000-6,500	261 hp @ 5,000-6,500	375 hp @ 5,200-6,700	434 hp @ 5,700-6,600
Maximum power @ engine speed	295 lb. - ft. @ 1,800 - 4,500	295 lb. - ft. @ 1,800 - 4,500	383 lb. - ft. @ 1,850	406 lb. - ft. @ 1,900
Maximum torque @ engine speed	6800 rpm	6800 rpm	6800 rpm	6800 rpm
Compression ratio	9.6:1	9.6:1	10.5:1	10.5:1
Power to weight ratio (lb/hp)	15.90	16.04	11.60	10.13
hp/liter	130.5	130.5	129.3	149.7
Chassis & Suspension				
Drivetrain	Active all-wheel drive (fully variable, hang-on)	Active all-wheel drive (fully variable, hang-on)	Active all-wheel drive (fully variable, hang-on)	Active all-wheel drive (fully variable, hang-on)
Front Axle	Aluminum 5-link	Aluminum 5-link	Aluminum 5-link	Aluminum 5-link
Rear Axle	Self-tracking trapezoidal link	Self-tracking trapezoidal link	Self-tracking trapezoidal link	Self-tracking trapezoidal link
Steering System	Power assisted, electromechanical	Power assisted, electromechanical	Power assisted, electromechanical	Power assisted, electromechanical
Turning Circle Diameter(ft)	39.2	39.2	39.2	39.2
Brakes & Wheels				
Caliper type (front/rear)	Aluminum monobloc fixed/floating	Aluminum monobloc fixed/floating	Aluminum monobloc fixed/floating	Aluminum monobloc fixed/floating
Rotor material	Steel, internally vented	Steel, internally vented	Steel, internally vented	PSCB, internally vented
Caliper color	Black	Black	Red	Red
Number of pistons (front/rear)	4/1	4/1	6/1	6/1
Rotor diameter (front/rear) mm	350/330	350/330	360/330	390/356
Wheel size and design	19" Macan Wheels	20" Macan S Wheels in Dark Titanium	20" Macan S Wheels in Polished/Dark Titanium	21" RS Spyder Design Wheels in Satin Black
Wheels and tires: front	19 x 8.5J ET21 235/55 R19	9J x 20 ET26 265/45 R20	9J x 20 ET26 265/45 R20	9.5J x 21 ET26 265/40 R21
Wheels and tires rear	19 x 9J ET21 255/50 R19	10J x 20 ET19 295/40 R20	10J x 20 ET19 295/40 R20	10J x 21 ET19 295/35 R21
Transmission				
Number of gears	7-speed	7-speed	7-speed	7-speed
Transmission type	PDK	PDK	PDK	PDK
1st	3.69	3.69	3.69	3.69
2nd	2.15	2.15	2.15	2.15
3rd	1.41	1.41	1.41	1.41
4th	1.03	1.03	1.03	1.03
5th	0.79	0.79	0.79	0.79
6th	0.63	0.63	0.63	0.63
7th	0.52	0.52	0.52	0.52
Reverse	2.94	2.94	2.94	2.94
Dimensions, Aerodynamics, & Weight				
Length (inches)	186.1	186.1	186.1	186.1
Wheelbase (inches)	110.5	110.5	110.5	110.5
Width w/ mirrors (inches)	82.6	82.6	82.6	82.6
Width w/o mirrors (inches)	75.9	75.9	75.9	75.9
Height (inches)	63.8	63.8	63.8	62.8
Drag coefficient (Cd)	0.36	0.36	0.37	0.36
Cargo area volume (cu.-ft.) seats up	22.0	22.0	22.0	22.0
Cargo area volume (cu.-ft.) seats down	53.1	53.1	53.1	53.1
Fuel tank capacity - refill volume (gal)	19.8	19.8	19.8	19.8
Curb weight (lbs)	4,149	4,187	4,350	4,398
Gross Vehicle Weight (lbs)	5,534	5,534	5,688	5,688
Payload (lbs) max	1,385	1,347	1,338	1,290
Towing Capacity Braked (lbs)	4,409	4,409	5,291	5,291
Towing Capacity Unbraked (lbs)	1,653	1,653	1,653	1,653
Performance				
Top track speed w/summer tires (mph)	144	144	160	169
0-60 /0-60 w launch control (mph)	6.0/5.8	na/5.8	4.6/4.4	4.3/4.1
Fuel Economy/Rating*				
City	19	19	17	17
Highway	25	25	23	22
Combined	21	21	19	19

*US EPA estimates. Actual mileage will vary.