

	911 Carrera (992.2)	911 Carrera Cabriolet (992.2)
Technical Data		
Engine		
Engine layout	Rear Engine	Rear Engine
Engine type	Boxer, twin-turbo	Boxer, twin-turbo
Cylinders	6	6
Valves per cylinder	4	4
Construction	Aluminum crankcase and heads	Aluminum crankcase and heads
Fuel injection	Direct Fuel Injection (DFI)	Direct Fuel Injection (DFI)
Fuel	Premium	Premium
Displacement (Liters)	3.0 l	3.0 l
Bore/Stroke (mm/mm)	91.0 mm / 76.4 mm	91.0 mm / 76.4 mm
Maximum power output @ engine speed	388 hp @ 6500	388 hp @ 6500
Maximum torque @ engine speed	331 lb.-ft. @ 2000-5000	331 lb.-ft. @ 2000-5000
Maximum engine speed	7500	7500
Compression ratio (tolerance +/- 0.3)	10.2 : 1	10.2 : 1
Output per liter	129.3	129.3
Lubrication	Integrated dry-sump	Integrated dry-sump
Power to weight ratio (lb/hp) (PDK / manual)	8.6	9.1
Drivetrain	Rear-wheel drive	Rear-wheel drive
Chassis & Suspension		
Body	Monocoque lightweight body in a combination of steel, aluminum, and magnesium	Monocoque lightweight body in a combination of steel, aluminum, and magnesium
Front Axle	MacPherson strut with anti-roll bar	MacPherson strut with anti-roll bar
Rear Axle	Aluminum multi-link with anti-roll bar	Aluminum multi-link with anti-roll bar
Steering System	Variable ratio electronic, power steering	Variable ratio electronic, power steering
Steering Ratio	15.0 : 1 (on-center) to 12.25 : 1	15.0 : 1 (on-center) to 12.25 : 1
Turning Circle	36.8 ft	36.8 ft
Brakes & Wheels		
Caliper type	Aluminum monobloc fixed-caliper brake	Aluminum monobloc fixed-caliper brake
Rotor material	Steel	Steel
Caliper color	Black	Black
Number of pistons (front/rear)	6 / 4	6 / 4
Rotor diameter (front/rear) mm	350 mm / 350 mm	350 mm / 350 mm
Rotor thickness (front/rear) mm	34 mm / 28 mm	34 mm / 28 mm
Standard wheel design	19" / 20" Carrera	19" / 20" Carrera
Standard wheel size (front/rear)	8.5J x 19" / 11.5J x 20"	8.5J x 19" / 11.5J x 20"
Standard tire size (front/rear)	235/40 ZR 19 / 295/35 ZR 20	235/40 ZR 19 / 295/35 ZR 20
Transmission		
Number of gears	8	8
Transmission type	8-speed dual-clutch PDK	8-speed dual-clutch PDK
Ratios		
1st	4.89	4.89
2nd	3.17	3.17
3rd	2.15	2.15
4th	1.56	1.56
5th	1.18	1.18
6th	0.94	0.94
7th	0.76	0.76
8th	0.61	0.61
Reverse	3.99	3.99
Rear Axle Ratio / rear constant transaxle ratio	3.39 / 0.92	3.39 / 0.92
Clutch 1/Clutch 2 diameter (inches)	8.7 / 6.6 inches (PDK)	8.7 / 6.6 inches (PDK)
Dimensions, Aerodynamics, & Weight		
Length (inches/mm)	178.8 in. / 4,542 mm	178.8 in. / 4,542 mm
Wheelbase (inches/mm)	96.5 in. / 2450 mm	96.5 in. / 2450 mm
Width w/ mirrors (inches/mm)	80.0 in. / 2033 mm	80.0 in. / 2033 mm
Width w/o mirrors (inches/mm)	72.9 in. / 1852 mm	72.9 in. / 1852 mm
Height with standard PASM suspension (inches/mm)	51.1 in. / 1298 mm	51.2 in. / 1,301 mm
Track width front (inches/mm)	62.7 in. / 1591 mm	62.7 in. / 1591 mm
Track width rear (inches/mm)	61.2 in. / 1557 mm	61.2 in. / 1557 mm
Cargo area volume (cu.-ft.) front trunk	132 l / 4.66 cu.-ft.	132 l / 4.66 cu.-ft.
Fuel tank capacity - refill volume (gal)	16.6 gal.	16.6 gal.
Curb weight (lbs)	3,342 lbs.	3,525 lbs.
Gross Vehicle Weight (lbs)	4,101 lbs.	4,442 lbs.
Payload range (lbs)	758 lbs.	917 lbs.
Performance		
Top track speed PDK (mph)	183 mph	181 mph
Acceleration 0-60 (sec)	3.9 sec.	4.1 sec.
Acceleration 0-60 PDK with Launch Control (sec)	3.7 sec.	3.9 sec.
Quarter mile time (sec)	12.3 sec.	12.5 sec.
Quarter mile time PDK with Launch Control (sec)	12.1 sec.	12.3 sec.
Fuel Economy/Rating		
Rating	-	-
City	18 mpg	18 mpg
Highway	25 mpg	25 mpg
Combined	21 mpg	21 mpg