

	Taycan	Taycan with Performance Battery Plus (PJK)	Taycan 4S	Taycan 4S with Performance Battery Plus (PJK)	Taycan GT5	Taycan Turbo	Taycan Turbo S	Taycan 4 Cross Turismo	Taycan 4S Cross Turismo	Taycan GT5 Sport Turismo	Taycan Turbo Cross Turismo	Taycan Turbo S Cross Turismo	
Technical Data	MY23 MSRP	\$86,700	\$92,480	\$106,500	\$112,070	\$134,100	\$153,300	\$187,400	\$97,700	\$113,000	\$136,000	\$155,900	\$190,000
Motor	Dual Motor, E-All Wheel Drive with Porsche Traction Management												
Drivetrain	Rear Motor, Rear Wheel Drive												
Motor type, front and rear	Permanent Magnet Synchronous Motor (PSM)												
Total maximum power kW (hp)	240, 300 with launch control (321, 402 with launch control)	280, 350 with launch control (375, 469 with launch control)	320, 390 with launch control (429, 522 with launch control)	360, 420 with launch control (482, 562 with launch control)	380, 440 with launch control (509, 590 with launch control)	460, 500 with launch control (616, 670 with launch control)	460, 560 with launch control (616, 750 with launch control)	280, 350 with launch control (375, 469 with launch control)	360, 420 with launch control (482, 562 with launch control)	380, 440 with launch control (509, 590 with launch control)	460, 500 with launch control (616, 670 with launch control)	460, 560 with launch control (616, 750 with launch control)	
Total maximum torque (lb.-ft.)	290, 264 with launch control	250, 263 with launch control	472	479	626	626	774	368	479	626	626	774	
Power to weight ratio (lbs/hp)	11.4	10.1	9.1	8.8	10.8	7.6	6.8	10.7	9.0	10.7	9.2	6.9	
Batteries	Lithium Ion Pouch configuration												
Cell type	723 volts / 129 Ah / 93.4 kWh												
Pack specification, maximum	613 volts / 129 Ah / 93.4 kWh	723 volts / 129 Ah / 93.4 kWh	613 volts / 129 Ah / 93.4 kWh	723 volts / 129 Ah / 93.4 kWh				723 volts / 129 Ah / 93.4 kWh					
Pack configuration	12 cells per module / 28 modules / 336 cells (168x2p)	12 cells per module / 33 modules / 396 total cells (198x2p)	12 cells per module / 28 modules / 336 cells (168x2p)	12 cells per module / 33 modules / 396 total cells (198x2p)				12 cells per module / 33 modules / 396 total cells (198x2p)					
Pack weight (lbs)	1,221	1,389	1,221	1,389				1,389					
Chassis & Suspension	Aluminum double wishbone, PASM												
Front axle	Aluminum multi-link axle with subframe, PASM												
Rear axle	Aluminum multi-link axle with subframe, PASM with adaptive air suspension												
Steering system	Electromechanical												
Steering ratio	Variable												
Turning circle (ft)	38.4 ft (36.7 ft with rear-axle steering)												
Brakes & Wheels	36.7 ft rear-axle steering std												
Caliper type	Fixed Aluminum Monoblock												
Rotor construction	Steel, internally vented												
Caliper color	Black	Red	White	White	Yellow	Black	Black	Red	Red	White	Yellow	Yellow	
Number of pistons (front/rear)	6/4	6/4	6/4	6/4	6/4	10/4	10/4	6/4	6/4	6/4	6/4	10/4	
Rotor diameter (front/rear) mm	360/358	360/358	390/358	410/366	420/410	360/358	360/358	410/365	410/365	360/358	410/365	420/410	
Rotor thickness (front/rear) mm	36/28	36/28	38/28	38/28	40/32	36/28	36/28	38/28	38/28	36/28	38/28	40/32	
Maximum Regenerative Braking Force	265 kW												
Wheel size and design	19" Taycan S Aero Wheels	19" Taycan S Aero Wheels	20" Taycan Turbo S Aero Design Wheels (Black)	20" Taycan Turbo S Aero Design Wheels	21" Mission-E Design Wheels	19" Taycan S Aero Wheels	19" Taycan S Aero Wheels	20" Taycan Turbo S Aero Design Wheels (Black)	20" Taycan Turbo Design Wheels	20" Taycan Turbo Design Wheels	20" Taycan Turbo Design Wheels	20" Taycan Turbo S Aero Design Wheels	
Wheels (front/rear)	(F) 8.0 X 19 ET 50 (R) 10.0 X 19 ET 47 (R) 225/35R19	(F) 8.0 X 19 ET 50 (R) 10.0 X 19 ET 47 (R) 225/35R19	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 1255/40R20	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 285/40R20	(F) 9.5 X 21 ET 60 (R) 11.5 X 21 ET 66 (R) 1265/35R21	(F) 8.0 X 19 ET 50 (R) 10.0 X 19 ET 47 (R) 225/35R19	(F) 8.0 X 19 ET 50 (R) 10.0 X 20 ET 47 (R) 1255/35R19	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 1255/40R20	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 1255/40R20	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 1255/40R20	(F) 9.0 X 20 ET 54 (R) 11.0 X 20 ET 60 (R) 1255/40R20	(F) 9.0 X 21 ET 60 (R) 11.0 X 21 ET 60 (R) 1265/40R20	
Tires (front/rear)	(R) 275/45R19	(R) 275/45R19	(R) 285/40R20	(R) 285/40R20	(R) 305/30R21	(R) 275/45R19	(R) 275/45R19	(R) 285/40R20	(R) 285/40R20	(R) 285/40R20	(R) 285/40R20	(R) 295/35R20	
Standard tire type	Summer tires												
Transmission	Two-speed dog-ring rear												
Transmission type	Single-speed front / Two-speed dog-ring rear												
Dimensions, Aerodynamics, & Weight	Single-speed front / Two-speed dog-ring rear												
Length (inches)	195.4	195.4	195.4	195.4	195.4	195.8	195.8	195.8	195.8	195.8	195.8	195.8	
Wheelbase (inches)	114.2	114.2	114.2	114.2	114.2	114.3	114.3	114.2	114.3	114.3	114.3	114.3	
Width w/mirrors (inches)	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	
Width (inches)	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	
Height (inches)	54.9	54.3	54.4	54.4	54.4	54.3	55.5	55.5	54.8	55.5	55.5	55.5	
Track width front (inches)	67.3	67.3	67.0	67.0	67.0	67.6	67.6	67.6	67.3	67.6	67.3	67.3	
Track width rear (inches)	66.7	66.7	65.7	65.7	65.7	65.2	66.9	66.9	65.8	66.7	65.8	65.8	
Drag coefficient (Cd)	0.24	0.23	0.24	0.23	0.23	0.23	0.27	0.26	0.26	0.26	0.26	0.26	
Approach/Departure angle (degrees)	12.1/15.2	11.2/14.3	11.2/14.8	11.2/14.8	11.2/14.8	12.2/16.2	12.2/16.2	12.2/16.2	11.2/14.8	12.3/16.5	12.3/16.5	12.2/16.2	
Rampover angle (degrees)	11.7	10.5	10.7	10.6	10.5	12	12	12	10.7	12.3	12.3	12	
Cargo area volume (cu.-ft.) front	2.9 cubic feet												
Cargo area volume (cu.-ft.) rear	14.3 cubic feet												
Curb weight (lbs)	4,566	4,742	4,771	4,947	5,077	5,119	5,101	5,029	5,033	5,152	5,196	5,199	
Gross Vehicle Weight (lbs)	6,162	6,162	6,349	6,349	6,283	6,349	6,327	6,360	6,338	6,349	6,349	6,349	
Payload, maximum (lbs)	1,596	1,420	1,402	1,402	1,206	1,230	1,226	1,331	1,327	1,186	1,153	1,150	
Performance	15.7 cu.-ft. / 42.8 cu.-ft. w/ seats folded												
Top track speed (mph)	143	143	155	155	161	161	136	149	155	155	155	155	
Acceleration 0-60 mph, w/Launch Control (sec)	5.1	5.1	3.8	3.8	3.5	3.0	2.6	4.8	3.9	3.5	3.1	2.7	
Acceleration 1/4 mile, w/Launch Control (sec)	13.7	13.5	12.3	12.2	11.1	10.7	11.1	12.2	11.8	11.8	11.1	10.7	
Charge Time, 0% - 100% SoC @ 9.6 kW (hrs)	9.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	
Charge Time, 0% - 100% SoC @ 19.2 kW (hrs)	4.8	5.3	4.8	4.8	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	
Charge Time, 5% - 80% SoC @ 50 kW (min)	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	19.0	
Charge Time, 5% - 80% SoC @ 225 kW (min)	22.5	N/A	22.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Charge Time, 5% - 80% SoC @ 270 kW (min)	N/A	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	
Fuel Economy Ratings	14.3 cu.-ft. / 41.3 cu.-ft. w/ seats folded												
MPGe (combined, city/hwy)	83, 79/88	82, 78/88	82, 82/82	80, 79/81	83, 83/82	81, 81/80	75, 74/74	80, 80/80	78, 78/78	80, 80/80	79, 80/78	75, 74/74	
Range (miles)	208	242	206	235	246	238	222	235	230	233	233	222	

*US EPA estimates. Actual mileage will vary.

Pricing, specifications, technical data, performance statistics, and the availability of particular vehicles and options are subject to change without notice. Prices listed in this document are manufacturer's suggested retail base prices, including options, destination charge, taxes, title, registration, and all other dealer charges. Actual prices are always set by authorized dealers.