Fuel and emissions

Fuel consumption combined (weighted) (WLTP)	1.7 – 1.4 l/100 km
Energy consumption combined (weighted) (WLTP)	31.6 – 29.2 kWh/100 km
CO ₂ emissions combined (weighted) (WLTP)	39 – 31 g/km
Electric range (EAER) (WLTP)	71 – 78 km
Electric range in town (EAER city) (WLTP)	80 – 89 km
Emissions standard	EU6 EA
Fuel type	Super Plus (98 RON)
Fuel tank capacity	70

Drive system

Туре	Parallel full hybrid with plug-in technology; combustion engine and hybrid module with electric motor and electromagnetic clutch
Maximum system power	382 kW (519 PS)
at engine speed	5,000 – 6,500 1/min
Maximum system torque	750 Nm
at engine speed	1,000 – 4,750 1/min

Combustion engine

Туре	V6 turbo; with petrol particulate filter
Number of cylinders	6
Valves per cylinder	4
Displacement	2,995 cm³
Bore	84.5 mm
Stroke	89.0 mm
Maximum power	260 kW (353 PS)
at engine speed	5,400 – 6,400 1/min
Maximum torque	500 Nm
at engine speed	1,450 – 4,500 1/min
Specific output	87 kW/I (118 PS/I)
Compression ratio	11.2:1
Maximum engine speed	6,500 1/min
Cooling system	Water cooling, thermal management with control thermostat
Valve control	VarioCam Plus: camshaft control on the inlet and outlet sides; valve lift switchover on the inlet side

Electric motor

Туре	Permanent magnet synchronous motor with external rotor
Maximum power	130 kW (176 PS)
at engine speed	3,200 1/min
Maximum torque	460 Nm
at engine speed	0 – 2,690 1/min

Plug-in system

Drive battery	Temperature-controlled lithium-ion battery
Energy capacity	25.9 kWh
Nominal voltage	370 V
Charger	On-board charger with 11 kW
Charging time (with 9.6 kW, 0-100 %)	approx. 3 h 15 min
Charging time (with 11 kW, 0-100 %)	approx. 2 h 39 min

Power transmission

	controlled and map-controlled multi-plate clutch, variable torque distribution between front and rear axle
Gearbox	Eight-speed Tiptronic S
Gear ratios	
1 th gear	4.71
2 th gear	3.14
3 th gear	2.11
4 th gear	1.67
5 th gear	1.29
6 th gear	1.00
7 th gear	0.84
8 th gear	0.67
Reverse gear	3.32
Rear-axle gear ratio	3.21

Chassis

Suspension and damping	Adaptive two-chamber air suspension with height adjustment; Porsche Active Suspension Management (PASM): electronically controlled damping system with two-valve dampers, continuous damper control and three manually selectable control maps
Front axle	Independent aluminium multi-link suspension
Rear axle	Independent aluminium multi-link suspension
Steering	Electromechanical Power Steering Plus
Steering ratio	13.3:1 (centre position)
Turning circle diameter	12.2 m
Vehicle stability system	Porsche Stability Management (PSM) with ABS, ASR, ABD, MSR and Trailer Stability Management

_	
Кra	KPS

Brake system	Hydraulic dual-circuit brake system with axle distribution; electric brake booster; electric duo-servo parking brake (EPB); auto-hold function; multi-collision brake; Porsche Hill Control (PHC)
Front brakes	Six-piston aluminium monobloc fixed-calliper brakes; grey cast-iron discs, internally vented
Diameter	410 mm
Thickness	38 mm
Rear brakes	Four-piston aluminium monobloc fixed-calliper brakes; grey cast-iron discs, internally vented
Diameter	365 mm
Thickness	28 mm

Wheels and tyres

Front wheels and tyres	9.0 J x 20 ET 50 with 255/55 ZR 20 tyres
Rear wheels and tyres	10.5 J x 20 ET 55 with 295/45 ZR 20 tyres

Dimensions

Length	4,930 mm
Width (including exterior mirrors)	1,983 mm (2,194 mm)
Height	1,657 mm
Wheelbase	2,895 mm
Front track width	1,680 mm
Rear track width	1,674 mm

Luggage compartment volume and weights

Luggage compartment volume	434 – 1,344 I
Unladen weight (DIN)	2,440 kg
Permissible gross weight	3,120 kg
Permissible trailer load (braked/unbraked)	3,500 kg/750 kg
Maximum towball load	140 kg
Permissible roof load (with Porsche roof transport system)	75 kg

Performance

Top speed	263 km/h
Top speed with electric motor only	135 km/h
Acceleration	
0 – 60 mph	4.4 s
0 – 100 km/h	4.7 s
0 – 160 km/h	10.6 s
0 – 200 km/h	16.8 s

Aerodynamics

Drag coefficient (c _d)	0.34
Cross-sectional area A	2.83 m²
c _d x A	0.962 m ²