


	Cayenne	Cayenne E-Hybrid	Cayenne S	Cayenne S E-Hybrid	Cayenne GTS	Cayenne Turbo E-Hybrid	Cayenne Coupe	Cayenne E-Hybrid Coupe	Cayenne S Coupe	Cayenne S E-Hybrid Coupe	Cayenne GTS Coupe	Cayenne Turbo E-Hybrid Coupe	Cayenne Turbo GT
													
MY2026 Cayenne Models													
Technical Data													
MSRP	\$89,900	\$103,100	\$108,300	\$111,600	\$132,400	\$164,500	\$95,100	\$107,300	\$114,900	\$117,100	\$137,100	\$169,100	\$214,800
Engine													
Engine layout	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine
Engine type	Turbocharged V6 90°	Turbocharged V6 90°	Twin-Turbo V8 90°	Turbocharged V6 90°	Twin-Turbo V8 90°	Twin-Turbo V8 90°	Turbocharged V6 90°	Turbocharged V6 90°	Twin-Turbo V8 90°	Turbocharged V6 90°	Twin-Turbo V8 90°	Twin-Turbo V8 90°	Twin-Turbo V8 90°
Displacement	2995	2995	3996	2995	3996	3996	2995	2995	3996	2995	3996	3996	3996
Maximum power output @ engine speed	348 @ 5,400 - 6,400	300 @ 5,400 - 6,400	468 hp @ 6,000	348 @ 5,400 - 6,400	493 hp @ 6,000	591 hp @ 6,000	348 hp @ 5,400 - 6,400	300 hp @ 5,400 - 6,400	468 hp @ 6,000	348 hp @ 5,400 - 6,400	493 hp @ 6,000	591 hp @ 6,000	650 hp @ 6,000
Maximum torque @ engine speed	368 lb.-ft. @ 1,500	309 lb.-ft. @ 1,400 - 4,800	442 lb.-ft. @ 2,000	368 lb.-ft. @ 1,500 - 4,500	486 lb.-ft. @ 2,100 - 4,500	590 lb.-ft. @ 2,400-4,500	368 lb.-ft. @ 1,500	309 lb.-ft. @ 1,400	442 lb.-ft. @ 2,000	368 lb.-ft. @ 1,500 - 4,500	486 lb.-ft. @ 2,100 - 4,500	590 lb.-ft. @ 2,400-4,500	626 lb.-ft. @ 2,300
Electric Motor max power @ rpm		174 hp @ 3,200		174 hp @ 3,200		174 hp @ 3,200				174 hp @ 3,200		174 hp @ 3,200	
Electric Motor max torque @ rpm		339 lb.-ft. @ 2,690		339 lb.-ft. @ 3,200		339 lb.-ft.				339 lb.-ft. @ 3,200		339 lb.-ft.	
Battery Size (Gross/Net) kWh		25.9/21.8		25.9/21.8		25.9/21.8				25.9/21.8		25.9/21.8	
Combined power		463 hp		512 hp @ 5,500 - 6,500		729 hp @ 5,500 - 6,800				463 hp		729 hp @ 5,500 - 6,800	
Combined torque		479 lb-ft		553 lb.-ft. @ 1,000 - 4,750		700 lb-ft @ 900 - 5,130				479 lb-ft		700 lb-ft @ 900 - 5,130	
Maximum engine speed	6,500	6,500	6,800	6,500	6,800	6,800	6,500	6,500	6,800	6,500	6,800	6,800	6,800
Compression ratio	11.2:1	11.2:1	9.7:1	11.2:1	9.7:1	9.7:1	11.2:1	11.2:1	9.7:1	11.2:1	9.7:1	9.7:1	9.7:1
Weight to Power ratio (lbs/hp)	13.4	11.6	10.4	10.4	10.4	10.4	13.6	11.7	10.6	10.5	10.5	10.5	7.8
Chassis & suspension													
Front Axle	Multi-Link Front Axle with Electromechanical Steering												
Rear Axle	Multi-Link Axle with Subframe and Dissolved Spring Damper Arrangement												
Steering System	Electromechanical Steering												
Brakes and Wheels													
Caliper type	Aluminum Monobloc Fixed Calipers front and rear												
Number of pistons (front/rear)	6 4	6 4	6 4	6 4	6 4	10 4	6 4	6 4	6 4	6 4	10 4	10 4	10 4
Caliper color	Black	Black	Red	Red	Red	Red	Black	Black	Red	Red	Red	Red	Yellow
Rotor design/material	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented/Cast	Internally vented and Cross
Rotor diameter (front rear) mm	390 358	410 358	410 358	410 365	410 365	420 365	390 358	410 358	410 358	410 365	410 365	420 365	440 410
Rotor thickness (front rear) mm	38 28	38 28	38 28	38 28	38 28	40 28	38 28	38 28	38 28	38 28	38 28	40 28	40 32
Name and option #	20" Cayenne Design wheels (43C)	20" AeroDesign wheels (57N)	20" Cayenne S wheels (57P)	20" Cayenne S wheels (57P)		21" Cayenne Turbo wheels (43G)	20" Cayenne Design wheels (43E)	20" AeroDesign wheels (57N)	20" Cayenne S wheels in Vesuvius Grey (V23)	20" Cayenne S wheels in Vesuvius Grey (V23)		21" Cayenne Turbo wheels (43G)	22" GT Design wheels in Satin Neodyme (47R)
Wheels	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.5J x 21 et 46 11.0J x 21 et 58	9.5J x 21 et 46 11.0J x 21 et 58	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.0J x 20 et 50 10.5J x 20 et 64	9.5J x 21 et 46 11.0J x 21 et 58	9.5J x 21 et 46 11.0J x 21 et 58	10.5J x 22 et 49 11.5J x 22 et 52
Tires	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	285/45 R 21 315/40 R 21	285/45 R 21 315/40 R 21	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	255/55 R 20 295/45 R 20	285/45 R 21 315/40 R 21	285/45 R 21 315/40 R 21	285/40 R 22 315/35 R 22
Transmission													
Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive
Number of gears	8	8	8	8	8	8	8	8	8	8	8	8	8
Transmission type	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic
Dimensions, Aerodynamics & Weight													
Length	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.1	194.2
Wheelbase	114	114	114	114	114	114	114	114	114	114	114	114	114
Width (mirrors folded/open)	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4
Height	66.9	66.8	66.8	66.8	66.8	66.4	66.1	65.9	66.1	66.5	66.5	66.5	65
Track width front	1676	66	66	66	66.5	66.5	66.5	66	66	66.5	66.5	66.5	66.6
Track width rear	1653	65.1	65.1	65.1	65.7	65.7	65.1	65.1	65.1	65.7	65.7	66.4	66.3
Drag coefficient (Cd)	0.36	0.36	0.35	0.35	0.35	0.35	0.36	0.36	0.36	0.35	0.35	0.35	0.37
Cargo Area Volume (cubic feet)	26.91	25.77	26.91	26.91	26.91	25.77	24.32	22.77	24.32	26.91	23.29	23.78	23.78
Cargo Area Volume (cubic feet) seats folded	60.31	55.19	60.31	60.31	54.98	53.04	47.46	53.04	47.46	60.31	47.46	52.47	52.47
Fuel Tank Capacity - refill volume (gal)	23.7	19.8	23.7	23.7	18.5	23.7	19.8	23.7	19.8	23.7	23.7	18.5	23.7
Curb weight (lbs)	4678	5348	4874	5311	4874	5664	4941	5415	4941	5377	4874	5719	5055
Max payload (lbs)	1572	1541	1585	1601	1585	1424	1477	1442	1475	1475	1585	1325	853
Max trailer load (braked/unbraked)	7716/1653	7716/1653	7716/1653	7716/1653	7716/1653	6613/1653	7716/1653	7716/1653	7716/1653	7716/1653	7716/1653	6613/1653	N/A
Suspension													
Suspension Type	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)	Adaptive Air Suspension (2C) w/PASM (2V)
(2 Valve / 2 Chamber)													
Ground Clearance (normal level/Terrain level)	8.3"	8.1"	8.2"	7.8"/9.5"	8.8"/11.0"	19.6"	8.4"	8.0"	8.3"	7.8"/9.5"	8.8"/11.0"	8.8"/11.0"	6.8"
Max Wading Depth (normal level/Terrain level)	19.6"	11.0"	19.6"	19.6"	24.2"	25.5"	11.0"	19.6"	11.0"	19.6"	24.2"	24.2"	18.1"
Approach Angle (normal level)	25.4°	25.6°	25.3°	17.6°/21.6°	18.5°	21.4°	25.5°	25.7°	25.3°	24.2°	24.2°	24.2°	17.6°
Breakover Angle (normal level)	18.9°	18.7°	18.8°	17.6°/21.6°	18.5°	21.4°	18.9°	18.9°	18.9°	17.6°/21.6°	18.9°	17.6°/21.6°	16.3°
Departure Angle (normal level)	22.3°	21.9°	22.1°	21.4°	22.5°	22.5°	21.7°	21.7°	22.3°	21.4°	21.4°	21.4°	18.8°
Performance													
Top Track Speed (mph) with optional summer tires	154	158	169	163	183	154	158	169	163	183	169	183	189
Acceleration 0 - 60/With Sport Plus (secs)	5.7/5.4	/4.6	4.7/4.4	/4.4	/3.5	/4.4	/5.4	/4.6	/4.4	/4.4	/4.4	/3.5	/3.1
1/4 mile from standing start (secs)	14.3/14.1	/13.2	13.2/13.1	/13.0	/11.7	/14.1	/13.2	/13.1	/13.1	/13.0	/13.1	/11.7	/11.6

212

208

210

214

8.35

8.19

8.27

8.43

204

212

173

8.03

8.35

6.81