Taycan 4S

Consumption, emissions, range (WLTP)

Electric energy consumption combined	20.7 – 17.7 kWh/100 km	
CO ₂ emissions combined	0 g/km	
CO ₂ class	А	
Electric range combined	474 – 557 km	
Electric range, city	528 – 617 km	

Drive system

Battery	High-voltage battery with 800 V rated voltage;
	energy content (gross): 89 kWh; energy content (net): 82.3 kWh
Electric motor, front axle	Permanent magnet synchronous motor
Electric motor, rear axle	Permanent magnet synchronous motor
Transmission, front axle	Single-speed transmission
Transmission, rear axle	Two-speed transmission
Drive system	All-wheel drive with electronically controlled Porsche Traction Management (PTM)
Power output 1)	Up to 340 kW (462 PS)
Overboost power with	Up to 400 kW (544 PS)
Launch Control ¹⁾	
Maximum torque with Launch	695 Nm
Control	

Chassis

Suspension and damping	Adaptive two-chamber air suspension with self-levelling system and height adjustment
	Porsche Active Suspension Management (PASM):
	Electronically controlled damping system with two-valve dampers,
	continuous damper control and three manually selectable modes
Front axle	Aluminium double-wishbone front axle
Rear axle	Aluminium multi-link suspension
Steering	Electromechanical Power Steering Plus
Steering ratio	15.1:1 (on-centre)
Turning circle diameter	11.7 m
Vehicle stability system	Porsche Stability Management (PSM) with ABS and extended brake functions

¹⁾ Details on the measurement procedure at www.porsche.com/gtr21

All data refers to the EU model (Germany). Technical data may vary depending on the country.

Taycan 4S

Brakes

Brake system	Porsche Recuperation Management;
	six-piston aluminium monobloc fixed-calliper brakes at the front,
	four-piston aluminium monobloc fixed-calliper brakes at the rear; electric parking brake, automatic hold function; multi-collision brake
Brake discs, front axle	Grey cast-iron brake discs, internally ventilated
Diar	neter 360 mm
Thick	ness 36 mm
Brake discs, rear axle	Grey cast-iron brake discs, internally ventilated
Diar	neter 358 mm
Thick	ness 28 mm

Wheels and tyres

Front wheels and tyres	8.0 J x 19 ET 50 with 225/55 R 19 tyres
Rear wheels and tyres	10.0 J x 19 ET 47 with 275/45 R 19 tyres

Dimensions

Length	4,963 mm
Width (including exterior mirrors)	1,966 mm (2,144 mm)
Height	1,379 mm
Wheelbase	2,900 mm
Front track width	1,710 mm
Rear track width	1,693 mm

Luggage compartment volume and weights

Luggage compartment volume (rear/front)	407 1/84 1
Unladen weight (DIN)	2,170 kg
Permissible gross weight	2,880 kg
Permissible roof load (with Porsche roof transport system)	75 kg

Taycan 4S

Performance

Top speed	250 km/h
Acceleration	
(with Launch Control)	
0 – 60 mph	3.5 s
0 – 100 km/h	3.7 s
0 – 160 km/h	8.1 s
0 – 200 km/h	12.5 s

Charging

Maximum charging capacity (DC)	Up to 270 kW
Charging time for direct current (DC, 800 V) with maximum charging capacity from 10 to up to 80 per cent under optimal conditions ²⁾	18 min
Recharged range (WLTP) in 10 mins at maximum charging power (800 V) under optimal conditions ³⁾	257 km
Charging time for direct current (DC, 400 V) with max. 135 kW charging capacity from 10 to up to 80 per cent	33 min
Recharged range (WLTP) in 10 mins at maximum charging power (400 V)	103 km
Charger (on-board charger)	11 kW
Charging time with alternating current (AC) at 11 kW from 0 to up to 100 per cent	9 hrs

Aerodynamics

Drag coefficient (c _d)	0.22
Frontal area A	2.33 m ²
c _d x A	0.513 m ²

²⁾ Optimal conditions: CCS fast-charging station of > 320 kW, > 850 V, battery temperature 23 °C and initial state of charge of nine per cent ³⁾ Optimal conditions: CCS fast-charging station with > 320 kW, > 850 V, battery temperature 23 °C and remaining range <30 km