Engine

<u> </u>	
Туре	V6 biturbo with gasoline particulate filter (GPF)
No. of cylinders	6
Valves/cylinder	4
Displacement	2,894 cm ³
Bore	84.5 mm
Stroke	86.0 mm
Max. power output	280 kW (380 PS)
at engine speed	5,200 – 6,700 rpm
Max. torque	520 Nm
at engine speed	1,750 – 5,000 rpm
Max. power output per litre	96.8 kW/I (131.3 PS/I)
Compression ratio	10.5:1
Max. engine speed	6,800 rpm
Cooling system	Water cooling, thermal management with control thermostat and potted water pump
Valve control	VarioCam Plus: Camshaft control on intake and exhaust sides, valve lift adjustment on the intake side

All data refers to the EU model. The technical data may vary from country to country

Power transmission

Drive system	Porsche Traction Management (PTM): Active all-wheel drive with electronically regulated, map-controlled multi-plate clutch, variable torque distribution between front and rear axle; switchable centre differential lock
Transmission	7-speed dual-clutch transmission (PDK)
Gear ratios .	
1 st gear	3.69
2 nd gear	2.15
3 rd gear	1.41
4 th gear	1.03
5 th gear	0.79
6 th gear	0.63
7 th gear	0.52
Reverse gear	2.94
Rear axle ratio	4.67

Chassis

Suspension and damping	Steel suspension lowered by 10 mm and double-acting, hydraulic gas-filled vibration dampers; Porsche Active Suspension Management (PASM) with continuous damper adjustment and three programmes
Front axle	Independent suspension with five-link aluminium front axle with separated wishbones at top and bottom
Rear axle	Independent suspension with aluminium trapezoidal link at the bottom, aluminium link at the top and tie rod
Steering	Electromechanical power steering
Steering ratio	14.3:1 (centre position)
Steering wheel diameter	375 mm
Turning circle diameter	11.96 m
Vehicle stability system	Porsche Stability Management (PSM) with ABS, ASR, ABD, EDTC and Trailer Stability Management

	Madan 616
Brakes	
Brake system	Six-piston aluminium monobloc fixed-calliper brakes at the front, combination floating-calliper brakes at the rear; electric parking brake; multi-collision brake
Brake discs, front axle	Internally vented cast-iron brake discs
Diameter	360 mm
Thickness	36 mm
Brake discs, rear axle	Internally vented cast-iron brake discs
Diameter	330 mm
Thickness	22 mm
Wheels and tyres	
Wheels with tyres, front	9J x 20 ET 26 with tyres 265/45 R 20
Wheels with tyres, rear	10J x 20 ET 19 with tyres 295/40 R 20
Dimensions	
Length	4,686 mm
Width (with exterior mirrors)	1,926 mm (2,098 mm)
Height	1,609 mm
Wheelbase	2,807 mm
Track width, front	1,650 mm
Track width, rear	1,658 mm
I	l
Luggage compartment vo	
	400 4 500 1

Luggage compartment volume 1)	488 – 1,503 l
Unladen weight according to DIN	1,910 kg
Permissible gross weight	2,580 kg
Trailer load (br./unbr.)	2,400/750 kg
Drawbar load	96 kg
Roof load (with Porsche roof transport system)	75 kg

Performance

Top speed	261 km/h
Acceleration	
0-60 mph	4.7 s
0-60 mph with Sport Plus	4.5 s
0-100 km/h	4.9 s
0-100 km/h with Sport Plus	4.7 s
0-160 km/h	11.6 s
0-160 km/h with Sport Plus	11.4 s
0-200 km/h	19.5 s
0-200 km/h with Sport Plus	19.3 s

Fuel and emissions

Emissions standard	Euro 6d-ISC-FCM (EU6 AP)
Fuel type	Super Plus (98 RON)
Fuel consumption	
Urban	12.1 I/100 km
Extra-urban	8.0 l/100 km
Combined	9.6 I/100 km ¹⁾ (9.5 I/100 km) ²⁾
CO ₂ emissions	
Combined	218 g/km ¹⁾ (216 g/km) ²⁾
Efficiency class Germany	E
Tank capacity (optional)	65 I (75 I)

¹⁾ Data does not apply to Denmark, France, Sweden, Iceland, Switzerland, Austria, Finland, Netherlands, Norway, Belgium, Malta/Cyprus ²⁾ Data applies only to Denmark, France, Sweden, Iceland, Switzerland, Austria, Finland, Netherlands, Norway, Belgium, Malta/Cyprus

Aerodynamics

Drag coefficient c _d	0.36
Frontal area A	2.62 m²
c _d x A	0.943 m²